

RADIO CONTROL ROLLING CODE

GB

SERIES: BeHAPPY RS

Radio control with variable 66 bit code transmission which guarantees an inviolable degree of security.

- Mod. **BeHappy RS 1** : one channel
- Mod. **BeHappy RS 2** : two channel
- Mod. **BeHappy RS 3** : three channel

TECHNICAL CHARACTERISTICS


- Powered by a lithium battery: 3Vdc (CR 2032)
- Working frequency: 433,92MHz
- Combinations: 66 bit rolling code
- Maximum consumption: <20mA
- Working temperature: -20÷55°C
- Dimensions: 33x69x13mm

DESCRIPTION OF FUNCTIONING

The transmitter, according to the model, is complete with either 1, 2 or 3 buttons for the management of either 1, 2 or 3 different uses.

WARNING

- The lithium battery Vdc (CR2032) must be changed every two years in order to guarantee the correct functioning of the transmitter.
- In order to substitute the dead battery, follow the illustration.
- The used battery must be disposed of correctly in an appropriate recycling bin.



SEAV s.r.l. declares that the products:

Radio control BeHappy RS 1

Radio control BeHappy RS 2

Radio control BeHappy RS 3

Comply with the requirements of the European Directive R&TTE 99/5/EC.



SEAV s.r.l.

Via S. Sabino, 34 - P.O. Box 14
60027 Osimo (AN) Italy
<http://www.seav.com>